



## GENESIS SERIES

# General Communications Cable HONEYWELL 4Pr Cat 5E CM Part No. 6330XXXX

### Description:

4 pair Category 5e unshielded twisted pair (UTP) cable, general communication UL 1685 rated ETL (or UL) Listed with 24 AWG solid bare copper conductors, polyethylene or polypropylene insulation, sunlight resistant RoHS compliant PVC jacket and a ripcord, 1000 - 0 (descending) footage marking. UL (or ETL) Verified to TIA/EIA-568 (Latest Revision) Category 5e and sweep tested to 350 MHz.

### Physical Information:

	CM	Conductor Color Code	Pair
Agency Listing:	CM	Blue & White/Blue	1
Insulation Type	HDPE or PP	Orange & White/Orange	2
Jacket Type	PVC	Green & White/Green	3
Jacket Diameter:	0.200"	Brown & White/Brown	4
Voltage Rating:	300 V		
Temperature Rating:	-20°C to 75°C		

### Print Legend\*:

HONEYWELL P/N 6330 4PR24 CAT 5E EEEEEEE (AAA) CL2 OR CM C(AAA)US  
SUN RES 75C (RoHS) BBB VERIFIED TO TIA-568-(NNN) CAT 5E XXXXXXXX YYYY FT RM# A  
B C D E F 1 2 3 4 5 6 7 8 9

EEEEEE – UL or ETL listing #

AAA – UL or ETL

BBB – Verification UL or ETL

NNN – Most Recent Revision of TIA/EIA – 568 Standard (i.e. 568-C.2)

XXXXXXX – Tracking #

YYYY – Countdown Footage Marking Number

### Electrical Characteristics:

Characteristic	Nominal Value	Maximum Value
DC Resistance	7.6 Ω/100m	9.38 Ω/100m
Resistance Unbalance	1.5%	5%
Capacitance	4.9 nF/100m	5.6 nF/100m
Capacitance Unbalance	50 pF/100m	330 pF/100m
Velocity of Propagation	69%	NA
Propagation Delay	515 ns/100m	570 ns/100m
Delay Skew	15 ns/100m	45 ns/100m

Frequency (MHz)	Impedance (Ohms)	Return Loss (Min, dB)	Insertion Loss (Max, dB/100m)	NEXT (Min, dB/100m)	PSNEXT (Min, dB/100m)	ACRF (Min, dB/100m)	PSACRF (Min, dB/100m)
0.772	100 +/- 15	19.4	1.8	67.0	64.0	66.0	63.0
1	100 +/- 15	20.0	2.0	65.3	62.3	63.8	60.8
4	100 +/- 15	23.0	4.1	56.3	53.3	51.8	48.8
8	100 +/- 15	24.5	5.8	51.8	48.8	45.7	42.7
10	100 +/- 15	25.0	6.5	50.3	47.3	43.8	40.8
16	100 +/- 15	25.0	8.2	47.2	44.2	39.7	36.7
20	100 +/- 15	25.0	9.3	45.8	42.8	37.8	34.8
25	100 +/- 15	24.3	10.4	44.3	41.3	35.8	32.8
31.25	100 +/- 15	23.6	11.7	42.9	39.9	33.9	30.9
62.5	100 +/- 15	21.5	17.0	38.4	35.4	27.9	24.9
100	100 +/- 15	20.1	22.0	35.3	32.3	23.8	20.8
155	100 +/- 20	18.8	28.1	32.4	29.4	20.0	17.0
200	100 +/- 22	18.0	32.4	30.8	27.8	17.8	14.8
350	100 +/- 25	16.3	44.9	27.1	24.1	12.9	9.9

Swept to 350 MHz, values beyond 100 MHz are for information only.